

In the Specification:

Page 7, after line 19, insert the following:

A<sub>1</sub> Figure 7 is an exploded view of a portion of the enlarged cross-section of the probe tip shown in Fig. 6.

line 20, change "7" to --8--;

line 23, change "8" to --9--;

line 24, change "7" to --8--; and

after line 25, insert the following:

--Figure 10 is an end view of the probe tip of the catheter

A<sub>2</sub> in the direction 10-10 of Fig. 9.

Page 8, line 1, change "Figure 9" to --Figures 11, 11a, 11b and 11c--, and change "is a schematic diagram" to --are schematic diagrams--.

NE Page 19, line 24, change "60-68" to--160-168--.

NE Page 20, line 1, change "60" to--160--;

NE Line 4, change "62" to--162--;

NE Line 5, change "64" to--164--;

NE Line 8, change "68" to--168--; and

NE Line 10, change "60-68" to--160-168--.

NE Page 21, line 21, change "58" to--158--.

NE Page 22, line 2, change "62" to--262--;

NE Line 3, change "62" to--262--;

NE Line 4, change "60" to--260--;

NE Line 5, change "64" to--264--;

NE Line 11, change "64" to--264--; and

NE Line 17 change "its inner surface 62" to--the inner surface of bore 262--.